

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
2 June 2005 (02.06.2005)

PCT

(10) International Publication Number
WO 2005/049281 A1

(51) International Patent Classification⁷: B25F 1/02,
3/00, B25D 17/28

(21) International Application Number:
PCT/AU2004/000360

(22) International Filing Date: 25 March 2004 (25.03.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003906460 24 November 2003 (24.11.2003) AU

(71) Applicant and

(72) Inventor: WHITEHEAD, John [AU/AU]; Colombo
Creek, Jerilderie, NSW 2716 (AU).

(74) Agent: RANTZEN, Henry, John; 85 John Street, Wool-
lahra, NSW 2025 (AU).

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,

CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,
GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:


— of inventorship (Rule 4.17(iv)) for US only

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: TWIN CHUCK DRILL WITH ONE DRIVE SHAFT



(57) Abstract: A pistol grip drill (1) has two control triggers (3 and 9) on its hand grip (4). One trigger (3) controls power to a motor in a casing (2) of the drill and the other trigger (9) initiates a sequence which interchanges the positions of two chucks (20, 21). The chucks (20, 21) are mounted on a forward extension (8) of the casing (2). The extension (8) has two degrees of freedom. It is firstly capable of rotating through ninety degrees about the axis of a pivot (14) to bring the unused chuck to the driving position in front of the casing (2). The second degree of freedom allows the extension to be then rotated about the driving axis of a drill drive shaft (5) so that the displaced chuck is moved from an upwardly-pointing position to a downwardly position directly in front of the pistol grip. The interchanging of the chucks (20, 21) can be controlled by the hand of the user holding the hand grip (4).

WO 2005/049281 A1